07530GA-24M-AA-00 NMB 24V 0.2A DC centrifugal blower fan

SKU: 07530GA-24M-AA-00

Price: \$9.99

Categories: Fans

Tags: NMB

Product Link:

https://www.elecspares.com/product/07530ga-24m-aa-00-nmb-24v-0-2a-dc-cen

trifugal-blower-fan/

Product Description

The NMB 07530GA-24M-AA-00 is a compact 24V DC centrifugal blower fan, Measuring 75mm x 75mm x 30mm, this blower is designed for effective cooling in confined spaces where directed airflow and moderate static pressure are needed, such as in control panels, network equipment, or small appliances. It operates at a rated voltage of 24V DC and, based on your input, draws a current of 0.20A, resulting in a power consumption of 4.8W. This model typically achieves a rotational speed of 3000 RPM, delivering an airflow of 10.5 CFM and a static pressure of 0.440 inch-H2O. Its noise level is 38.5 dBA. The fan features ball bearings for enhanced durability and a reliable operational lifespan of 70,000 hours at 25°C. It comes with 2-wire leads and includes auto-restart and polarity protection.

Model Number: 07530GA-24M-AA-00

Manufacturer: NMB Technologies Corporation

Series: 07530GA Series

Type: DC Blower Fan (Centrifugal Fan)

Dimensions: 75.7mm L x 75.7mm H x 30mm W

Rated Voltage: 24V DC

Operating Voltage Range: 10.0V to 26.0V DC

Rated Current: 0.20A

Rated Power: 4.8W (calculated: 24V * 0.20A)

Speed: 3000 RPM

Airflow: 10.5 CFM (0.30 m³/min)

Static Pressure: 0.440 inch-H2O (110 Pa)

Noise Level: 38.5 dBA Connector: 2-Wire Leads Bearing Type: Ball Bearing

Life Expectancy: 70,000 hours at 25°C (L10 Life)

Frame Material: Plastic (Black, UL94V-0)

Impeller (Blade) Material: Plastic (Black, UL94V-0)

Features: Auto Restart, Polarity Protection Operating Temperature: -10°C to +60°C

Weight: 90g

Approvals/Certifications: UL, CSA, TUV, CE, RoHS Compliant

Product Images







Scan for product details:

