

4715KL-05W-B30-P00 NMB 24V 0.40A 120mm DC Axial Fan

SKU: 4715KL-05W-B30-P00

Price: \$21.99

Categories: Fans

Tags: NMB

Product Link:

<https://www.elecspares.com/product/4715kl-05w-b30-p00-nmb-24v-0-40a-120mm-dc-axial-fan/>

Product Description

The NMB 4715KL-05W-B30-P00 is a high-performance 24 V industrial axial fan with dimensions of 120 x 120 x 38 mm, purpose-built to deliver elite-level thermal cooling in high-resistance airflow paths. This unit features a heavy-duty brushless DC motor capable of sustaining a 9.6 W power input to drive its specialized 7-blade impeller at a consistent 3300 RPM. Engineered specifically for high-torque air displacement in mission-critical hardware, it utilizes a robust fiberglass-reinforced PBT structure to ensure consistent heat dissipation under heavy thermal loads. The mechanical design relies on a precision-shielded dual ball bearing system to ensure 50,000 hours of continuous operation at a 25 °C ambient temperature. Featuring a simplified 2-wire electrical interface for direct power connection, this fan is a critical component for industrial workstations, networking hubs, and power converters where long-term reliability and high-velocity cooling are mandatory.

4715KL-05W-B30-P00 Fan Parameters

Manufacturer: NMB-MAT (MinebeaMitsumi)

Model Number: 4715KL-05W-B30-P00

Series: 715KL Series

Industry Size Code: 12038

Type: DC Axial Fan

Bearing Type: Dual Ball Bearing

Nominal Voltage: 24 VDC

Voltage Range: 14.0 - 27.6 VDC

Starting Voltage: 14.0 VDC

Dimensions: 120 x 120 x 38 mm

Weight: 260 g

[Electrical Data]

Input Power: 9.6 W

Nominal Current: 0.40 A

Max. Current: 0.60 A (Peak during startup)

Nominal Speed: 3300 RPM (Tolerance $\pm 10\%$)

Motor Design: Brushless DC Motor

Signal Output: None (2-Wire configuration)

Motor Protection: Auto Restart, Polarity Protection, Locked Rotor Protection

Insulation Class: Class E

Insulation Resistance: $>10M$ ohm at 500 VDC

Dielectric Strength: 700 VAC for 1 minute

Termination: 2-Lead wires (UL1007, AWG 24, Red/Black)

[Performance & Acoustics]

Max. Air Flow: 105.9 CFM (180.0 m^3/h / 3.00 m^3/min)

Max. Static Pressure: 9.07 mmH₂O (89.0 Pa / 0.36 inH₂O)

Sound Pressure Level: 46.5 dB(A) (Measured at 1 meter)

Number of Blades: 7

Direction of Rotation: Clockwise (viewed toward rotor)

Airflow Direction: Intake over struts

[Materials & Construction]

Frame Material: Plastic (PBT reinforced with 30% glass fiber, UL94V-0)

Impeller Material: Plastic (PBT reinforced with 15% glass fiber, UL94V-0)

Installation Position: Any

Degree of Protection: IP20

[Reliability & Safety Standards]

Min. Ambient Temperature: -10 °C

Max. Ambient Temperature: 70 °C

Storage Temperature: -40 °C - 70 °C

Life Expectancy (L10): 50,000 hours at 25 °C

Standard Compliance: UL 507, CSA C22.2, EN 60950-1

Approval Agency: UL, CUL, TUV, CE, RoHS

Application

The NMB 4715KL-05W-B30-P00 axial fan is used in industrial power supplies, telecommunications base stations, professional audio amplifiers, server enclosure ventilation, and automated test equipment.

Product Images



Scan for product details:



