

H3200ZE XIMADEN DCB relay

SKU: 19689630582

Price: \$31.43

Categories: Relays

Tags: Ximaden

Product Link:

<https://www.electspares.com/product/h3200ze-ximaden-dcb-relay/>

Product Description

H3200ZE High thermal conductivity DCB module relay directly sent to XIMADEN tempering furnace by Beijing Shimanton Company

1. Base plate material: DBC copper-ceramic bonding
2. Silicon wafer: glass passivated thyristor
3. Welding layer: two layers (low thermal resistance)
4. Internal protection material: high sealing and high soft silicone gel
5. Cleaning after welding: very clean
6. Thermal stability test (125 degrees) long-term stability
7. Leakage current test: Reverse leakage current < 10mA
8. Large current test: Good thermal matching and small deformation
9. Heat dissipation medium: patented thermal pad
10. Thermal pad application mark: Application of DBC and thermal pad

Additional Information

sort by color: H3200ZE (zero-crossing type) 4-24VDC, H3200PE (random type) 4-12VDC, H3200ZE (24V special type) requires communication when ordering, H3200PE4-12VDC, H3200ZE 4-32VDC

Product Images





高导热 DCB 基板

增强型固态继电器



产品型号:	H3200ZE
控制电压:	4-24V
控制电流:	>8mA
输出电压范围:	40-480V
标称电流:	200A
通态峰值电压:	<1.5V
断态漏电流:	<3mA
触发方式:	过零触发
安装方式:	螺丝安装
工作指示:	LED
环境温度:	-30℃~50℃

增强型固态继电器



产品型号:	H3200ZE
控制电压:	4-24V
控制电流:	>8mA
输出电压范围:	40-430V
标称电流:	200A
通态峰值电压:	<1.5V
断态漏电流:	<3mA
触发方式:	过零触发
安装方式:	螺丝安装
工作指示:	LED
环境温度:	-30℃~50℃

Scan for product details:

