## KA1238XA2 KAKU 220-240V AC axial fan

**SKU:** KA1238XA2

**Price:** \$13.46

Categories: Fans

Tags: KAKU

**Product Link:** 

https://www.elecspares.com/product/ka1238xa2-kaku-220-240v-ac-axial-fan/

## **Product Description**

The KAKU KA1238XA2 is an AC axial fan measuring 120x120x38mm. It operates on 220-240 VAC at both 50 Hz and 60 Hz frequencies, drawing 0.15 A of current at 50 Hz and 0.13 A at 60 Hz. Power consumption is 34.5 W at 50 Hz and 29.9 W at 60 Hz. This fan achieves a speed of 2500 RPM at 50 Hz and 2800 RPM at 60 Hz, providing an airflow of 80 CFM at 50 Hz and 110 CFM at 60 Hz. The noise level is 40 dB(A) at 50 Hz and 45 dB(A) at 60 Hz. It is equipped with ball bearings for durable operation and features 2-wire leads. Constructed with an aluminum frame and plastic impeller, it is designed for general cooling and ventilation in industrial equipment, power supplies, and control cabinets.

KA1238XA2 Fan Parameters

Model: KA1238XA2 Manufacturer: KAKU Type: AC Axial Fan

Dimensions: 120x120x38 mm Rated Voltage: 220-240 VAC Frequency: 50 Hz / 60 Hz

Rated Current (50Hz / 60Hz): 0.15 A / 0.13 A

Power Consumption (50Hz / 60Hz): 34.5 W / 29.9 W

Speed (50Hz / 60Hz): 2500 RPM / 2800 RPM Airflow (50Hz / 60Hz): 80 CFM / 110 CFM

Static Pressure: 0.28 in H2O

Noise Level (50Hz / 60Hz): 40 dB(A) / 45 dB(A)

Bearing Type: Ball Bearing Termination: 2-wire leads

Weight: 0.55 kg

Frame Material: Die-cast aluminum

Impeller Material: Plastic

Operating Temperature:  $-10^{\circ}$ C to  $+70^{\circ}$ C

Life Expectancy: 50,000 hours

Motor Protection: Impedance Protected

Approval Agency: CE

Application: Industrial equipment, power supplies, control cabinets, general cooling.

## **Product Images**









Scan for product details:

