

# KA1725HA1 KAKU 110-120V AC axial fan

**SKU:** KA1725HA1

**Price:** \$17.49

**Categories:** Fans

**Tags:** KAKU

**Product Link:**

<https://www.electspares.com/product/ka1725ha1-kaku-110-120v-ac-axial-fan/>

---

## Product Description

---

The KAKU KA1725HA1 is an AC axial fan measuring 172x150x51mm. It operates on 110-120 VAC at both 50 Hz and 60 Hz frequencies, drawing 0.65 A of current at 50 Hz and 0.55 A at 60 Hz. Power consumption is 74.8 W at 50 Hz and 63.3 W at 60 Hz. This fan achieves a speed of 2800 RPM at 50 Hz and 3000 RPM at 60 Hz, providing an airflow of 194.6 CFM at 50 Hz and 218.2 CFM at 60 Hz, with a static pressure of 0.31 in H<sub>2</sub>O at 50 Hz and 0.51 in H<sub>2</sub>O at 60 Hz. The noise level is 52.3 dB(A). It is equipped with ball bearings for durable operation and features 2-wire terminals or leads. Constructed with an aluminum frame and steel or magnesium impeller, it is designed for cooling industrial cabinets and various electronic equipment.

### KA1725HA1 Fan Parameters

Model: KA1725HA1

Manufacturer: KAKU

Type: AC Axial Fan

Dimensions: 172x150x51 mm

Rated Voltage: 110-120 VAC

Frequency: 50 Hz / 60 Hz

Rated Current (50Hz / 60Hz): 0.65 A / 0.55 A

Power Consumption (50Hz / 60Hz): 74.8 W / 63.3 W

Speed (50Hz / 60Hz): 2800 RPM / 3000 RPM

Airflow (50Hz / 60Hz): 194.6 CFM / 218.2 CFM

Static Pressure (50Hz / 60Hz): 0.31 in H<sub>2</sub>O / 0.51 in H<sub>2</sub>O

Noise Level: 52.3 dB(A)

Bearing Type: Ball Bearing

Weight: 0.805 kg

Frame Material: Die-cast aluminum

Impeller Material: Steel or Magnesium

Operating Temperature: -40°C to +80°C

Life Expectancy: 50,000 hours

Motor Protection: Shaded pole impedance protection

Approval Agency: UL, CE

Application: Industrial cabinets, electronic equipment cooling, ventilation.

## Product Images

---









---

Scan for product details:

