

KA2060HA2 KAKU card 220-240V 0.26A waterproof fan

SKU: KA2060HA2

Price: \$59.69

Categories: Fans

Tags: KAKU

Product Link:

<https://www.electspares.com/product/ka2060ha2-kaku-card-220-240v-0-26a-waterproof-fan/>

Product Description

KA2060HA2 original genuine KAKU card 220-240V 0.26A waterproof cooling fan

The KAKU KA2060HA2 is an AC axial fan measuring 200x200x60mm. It operates on 220-240 VAC at 50/60 Hz frequencies, drawing 0.26 A of current. Power consumption is typically 38 W at 50 Hz and 40 W at 60 Hz. This fan achieves a speed of 2800 RPM at 50 Hz and 3200 RPM at 60 Hz, providing an airflow of 400 CFM at 50 Hz and 425 CFM at 60 Hz, with a noise level of 60 dB(A) at 50 Hz and 65 dB(A) at 60 Hz. It is equipped with ball bearings for durable operation and features 2-wire leads. Constructed with an aluminum frame and plastic impeller, it is designed for high-volume air movement in industrial equipment, control cabinets, and various cooling applications.

KA2060HA2 Fan Parameters

Model: KA2060HA2

Manufacturer: KAKU

Type: AC Axial Fan

Dimensions: 200x200x60 mm

Rated Voltage: 220-240 VAC

Operating Voltage Range: Not specified

Frequency: 50 Hz / 60 Hz

Rated Current: 0.26 A

Power Consumption (50Hz / 60Hz): 38 W / 40 W

Speed (50Hz / 60Hz): 2800 RPM / 3200 RPM

Airflow (50Hz / 60Hz): 400 CFM / 425 CFM

Static Pressure: Not specified

Noise Level (50Hz / 60Hz): 60 dB(A) / 65 dB(A)

Bearing Type: Ball Bearing (Dual Ball Bearing often specified)

Termination: 2-wire leads

Weight: Not specified

Frame Material: Die-cast aluminum

Impeller Material: Plastic

Operating Temperature: -15°C to +70°C (for Topfan MX20060ABH22)

Life Expectancy: 50,000 to 100,000 hours (for ball bearing)

Motor Protection: Impedance Protected (often for similar models)

Approval Agency: CE, RoHS

Application: Industrial equipment, control cabinet cooling, power supply units, ventilation systems.







Product Images







Scan for product details:

