

KA2072HA2 KAKU 220-240V AC axial fan

SKU: KA2072HA2

Price: \$60.55

Categories: Fans

Tags: KAKU

Product Link:

<https://www.electspares.com/product/ka2072ha2-kaku-220-240v-ac-axial-fan/>

Product Description

The KAKU KA2072HA2 is an AC axial fan measuring 205x205x72mm. It operates on 220-240 VAC at both 50 Hz and 60 Hz frequencies, drawing 0.40 A of current at 50 Hz and 0.42 A at 60 Hz. Power consumption is 92 W at 50 Hz and 97 W at 60 Hz. This fan achieves a speed of 2900 RPM at 50 Hz and 3300 RPM at 60 Hz, providing a high airflow of 850 CFM at 50 Hz and 930 CFM at 60 Hz. The noise level ranges from 69 dB(A) at 50 Hz to 72 dB(A) at 60 Hz. It is equipped with ball bearings for durable operation and commonly features 2-wire termination. Constructed with an aluminum or magnesium alloy frame and impeller, it is often designed for high temperature resistance, making it suitable for server cabinets, power electronics, and industrial cooling.

KA2072HA2 Fan Parameters

Model: KA2072HA2

Manufacturer: KAKU

Type: AC Axial Fan

Dimensions: 205x205x72 mm

Rated Voltage: 220-240 VAC

Frequency: 50 Hz / 60 Hz

Rated Current (50Hz / 60Hz): 0.40 A / 0.42 A

Power Consumption (50Hz / 60Hz): 92 W / 97 W

Speed (50Hz / 60Hz): 2900 RPM / 3300 RPM

Airflow (50Hz / 60Hz): 850 CFM / 930 CFM

Static Pressure: 0.86 in H₂O

Noise Level (50Hz / 60Hz): 69 dB(A) / 72 dB(A)

Bearing Type: Ball Bearing

Termination: 2-wire leads

Weight: 2.1 kg

Frame Material: Die-cast aluminum or Magnesium alloy

Impeller Material: Metal

Operating Temperature: -10°C to +80°C

Life Expectancy: 50,000 hours

Motor Protection: Impedance Protected

Approval Agency: CE, RoHS

Application: Industrial equipment, server cabinets, power electronics, HVAC systems, high-temperature environments.

Product Images









Scan for product details:

