

KAKU KA1238HA2B FU-9803C FU-9803A full metal double ball fan

SKU: 19431378951

Price: \$15.00

Categories: Fans

Tags: KAKU

Product Link:

<https://www.electspares.com/product/kaku-ka1238ha2b-fu-9803c-fu-9803a-full-metal-double-ball-fan/>

Product Description

Model: KA1238HA2

Dimensions: 120x120x38mm

Voltage: 220/240V

Current/Power: 0.13/0.11A

Air Volume: 80/100CFM

Air Pressure: 0.303INH2O

Speed: 2700/3100RPM

Noise: 49/51dB(A)

Weight: 460G

Lifespan: 30000H

Bearing Structure: Ball Bearing

Wiring: Terminal

Temperature Range: -20°C to +80°C

Frame: Magnesium Alloy

Taiwan original Taiwan KAKU FU-9803C FU-9803A KA1238HA2B full metal double ball fan

Here is the technical specification for KAKU FU-9803C/FU-9803A/KA1238HA2B in English:

I. Core Component Configuration

FU-9803C Fan Assembly

Combination of FU-9803A filter unit and KA1238HA2B axial fan

Available in ball bearing or sleeve bearing versions, supports blade/lead wire connection

FU-9803A Filter Unit

Frame material: ABS resin (flame-retardant, UV-resistant)

Filter media: Imported nylon fiber composite resin, 80% dust removal efficiency

Compatible fans: KA1238HA2B (120×120×38mm) etc.

KA1238HA2B Axial Fan

Voltage: AC220V±10% (50/60Hz)

Power: 21W (50Hz)/18W (60Hz)

Dimensions: 120×120×38mm

Bearing: Ball bearing

Speed: 2700r/min (50Hz)/3100r/min (60Hz)

Airflow: 84CFM (50Hz)/100CFM (60Hz)

Noise: 49dB (50Hz)/51dB (60Hz)

II. Performance & Certification

Insulation class: F (155°C rated)

Lifetime: 35,000 hours L10 at 25°C

Protection rating: IP44 (louver design)

III. Extended Compatibility

Can be paired with FU-9801A P3 protective cover for enhanced protection

For 380V version, select KA1238HA3 model

Note: All specifications are based on standard operating conditions at sea level. Performance may vary with environmental factors.

Product Images



风机+原装单片塑胶网+螺丝包



KA1238HA2SMT 含油轴承 AC220V





Scan for product details:

