

MA2062-HVL GN SUNON 220-240V AC axial fan

SKU: MA2062-HVL GN

Price: \$14.46

Categories: Fans

Tags: SUNON

Product Link:

<https://www.electspares.com/product/ma2062-hvl-gn-sunon-220-240v-ac-axial-fan/>

Product Description

The SUNON MA2062-HVL GN is an AC axial fan measuring 60x60x25mm, designed for efficient and quiet cooling. Operating on 220-240 VAC at 50/60 Hz, this fan utilizes MagLev technology and a Vapo bearing system to deliver superior performance, low noise, and extended life.

Depending on the frequency, it draws between 198 mA and 211 mA, with power consumption ranging from 4.1 W to 4.4 W. It achieves speeds between 4100 RPM and 4200 RPM, providing airflow from 29.7 m³/h (17.5 CFM) to 30.6 m³/h (18 CFM), with noise levels between 30 dB(A) and 31 dB(A). Connecting via 2 wire leads, its robust construction with thermoplastic (PBT) housing and impeller, and a UL94V-0 flammability rating, makes it ideal for various electronic equipment and applications requiring a durable and quiet cooling solution.

MA2062-HVL GN Fan Parameters

Model: MA2062-HVL GN

Manufacturer: SUNON

Type: AC Axial Fan

Dimensions: 60x60x25 mm

Rated Voltage: 220-240 VAC

Frequency: 50/60 Hz

Rated Current: 198 mA (50 Hz) / 211 mA (60 Hz)

Power Consumption: 4.1 W (50 Hz) / 4.4 W (60 Hz)

Speed: 4100 RPM (50 Hz) / 4200 RPM (60 Hz)

Airflow: 29.7 m³/h (17.5 CFM) (50 Hz) / 30.6 m³/h (18 CFM) (60 Hz)

Static Pressure: 0.19 inH₂O (50 Hz) / 0.20 inH₂O (60 Hz)

Noise Level: 30 dB(A) (50 Hz) / 31 dB(A) (60 Hz)

Bearing Type: Vapo Bearing

Termination: 2 Wire Leads

Housing Material: Thermoplastic (PBT)

Impeller Material: Thermoplastic (PBT)

Flammability Rating: UL94V-0

Operating Temperature: -10 to 70°C

Expected Life: 60,000 hours (at 40°C)

Motor Protection: Impedance protected, auto-restart

Weight: 81 g

Application: Electronic equipment, general cooling and ventilation.

Product Images









Scan for product details:

