

# MDS-C1-CV-75/55/110/150/220/260/300/370 Mitsubishi driver

**SKU:** 742539773016

**Price:** \$1,285.65

**Categories:** CNC

**Tags:** Mitsubishi

**Product Link:**

<https://www.electspares.com/product/mds-c1-cv-75-55-110-150-220-260-300-370-mitsubishi-driver/>

---

## Product Description

---

MDS-C1-CV-75/55/110/150/220/260/300/370 Mitsubishi driver

## Additional Information

---

**sort by color:** MDS-C1-CV-75, MDS-C1-CV-55, MDS-C1-CV-110, MDS-C1-CV-150, MDS-C1-CV-220, MDS-C1-CV-260, MDS-C1-CV-300, MDS-C1-CV-370

## Product Images

---



REFER TO MANUAL BEFORE  
INSTALLING OR SERVICING



BAUART  
GEPRÜFT  
TYPE  
APPROVED



**MITSUBISHI**

POWER DRIVE UNIT

TYPE

**MDS-C1-CV-260**

POWER 26KW  
INPUT 95A 3PH 200/200-230V 50/60Hz  
0.2A 1PH 200/200-230V 50/60Hz  
OUTPUT 115A DC270-311V  
EN50178 MANUAL# BNP-B3000  
S/W BND528W000B2 H/W VER N

MITSUBISHI ELECTRIC CORPORATION  
TOKYO 100-830 JAPAN

MADE IN JAPAN

## WARNING



**警告**

- HAZARDOUS VOLTAGE
- DO NOT TOUCH DRIVE UNIT AND WIRING WITHIN 15MIN.AFTER POWER OFF. DISCHARGE TIME IS APPROX.15MIN.
- ONLY RCD OF TYPE B IS ALLOWED. SEE THE MANUAL FOR DETAILS.
- ALWAYS CONNECT PROTECTIVE EARTH(PE) TERMINAL FOR PROTECTION AGAINST ELECTRIC SHOCK.
- SUPPLY NEUTRAL NEEDS TO BE EARTHED.

- ・高電圧注意
- ・電源遮断後15分間は、ユニット及び配線に手を触れしないで下さい。放電に約15分かかります。
- ・交流、直流両検出可能な漏れ電流装置を使用して下さい。
- ・詳細に関してはマニュアルを見てください。
- ・感電防止の為、保護アース ( PE ) 端子の接続を必ず行つて下さい。
- ・欧州で使用する場合は中性点接地の電源を使用して下さい。







Scan for product details:

