

# PMB1212PLB2-A(2).GN SUNON 12V 9.8W blower fan

**SKU:** PMB1212PLB2-A(2).GN

**Price:** \$13.65

**Categories:** Fans

**Tags:** SUNON

**Product Link:**

<https://www.electspares.com/product/pmb1212plb2-a2-gn-sunon-12v-9-8w-blower-fan/>

---

## Product Description

---

The Sunon PMB1212PLB2-A(2).GN is a robust DC Blower Fan engineered for effective thermal management in applications where high static pressure is critical. Operating on 12V DC power, it draws 0.82A of current, resulting in a 9.8W power consumption. Measuring 120mm x 120mm x 32mm, this fan spins at 2500 RPM, delivering a substantial 35.9 CFM of airflow and an impressive static pressure of 0.89 inH<sub>2</sub>O, allowing it to efficiently move air even through restrictive pathways. It produces a noise level of 53.8 dBA, which is typical for a blower of its performance class. Equipped with 2-wire leads and built with durable dual ball bearings, the PMB1212PLB2-A(2).GN ensures reliable operation with an auto-restart function and is RoHS compliant, making it a suitable choice for cooling in systems like servers, networking equipment, and industrial machinery.

PMB1212PLB2-A(2).GN built SUNON turbine blower 12032 centrifugal fan 12V 9.8W

Manufacturer: Sunon

Model Number: PMB1212PLB2-A(2).GN

Type: DC Blower Fan

Rated Voltage: 12V DC

Operating Voltage Range: 6V to 13.8V DC

Rated Current: 0.82A

Rated Power: 9.8W

Speed: 2500 RPM

Airflow: 35.9 CFM

Static Pressure: 0.89 inH<sub>2</sub>O or 221.7 Pa

Noise Level: 53.8 dBA

Dimensions: 120mm x 120mm x 32mm

Connector: 2-Wire Leads

Bearing Type: Dual Ball Bearing

Features: Auto-restart, RoHS compliant

Operating Temperature: -10°C to 70°C

Material: Polybutylene Terephthalate (PBT) for both frame and impeller

Flammability Rating: UL94V-0

## Product Images

---









---

Scan for product details:

