

# PMD2408PMB3-A.(2).GN Sunon 24V DC Axial Fan

**SKU:** PMD2408PMB3-A.(2).GN

**Price:** \$9.99

**Categories:** Fans

**Tags:** SUNON

**Product Link:**

<https://www.electspares.com/product/pmd2408pmb3-a-sunon-24v-dc-axial-fan/>

---

## Product Description

---

The Sunon PMD2408PMB3-A.(2).GN is a 24VDC axial fan with dimensions of 80x80x38mm. It operates within a 10-27.6VDC working voltage range, drawing 0.20A of current and consuming 4.8W of power. This fan provides 59.5CFM (approximately 101.1m<sup>3</sup>/h) of airflow and can generate 0.43inchH<sub>2</sub>O (approximately 107.1Pa) of static pressure. The fan runs at a speed of 4200RPM, with a noise level of 47.3dB(A). It uses durable ball bearings and a two wire lead connection. The fan is constructed with a thermoplastic plastic housing and impeller. It is suitable for ambient temperatures ranging from -10 to 70°C.

### PMD2408PMB3-A Fan Parameters

Manufacturer: Sunon

Model: PMD2408PMB3-A.(2).GN

Fan Type: DC Axial Fan

Dimensions: 80 x 80 x 38 mm

Rated Voltage: 24 VDC

Operating Voltage Range: 10 ~ 27.6 VDC

Current Rating: 0.20 A

Power Consumption: 4.8 W

Airflow: 59.5 CFM (101.1 m<sup>3</sup>/h)

Static Pressure: 0.43 inch H<sub>2</sub>O (107.1 Pa)

Speed: 4200 RPM

Noise Level: 47.3 dB(A)

Bearing Type: Ball Bearing

Termination: Two Wire Leads

Housing Material: Plastic (Thermoplastic)

Impeller Material: Plastic (Thermoplastic)

Operating Temperature: -10 ~ 70°C

Weight: 175 g

Approval Agency: CE, UL, cURus, TUV

Application: This Sunon DC axial fan is suitable for cooling applications in various electronic equipment, power supplies, and industrial control systems, especially where efficient airflow in a compact space is required.

## Product Images

---









---

Scan for product details:

