

W3G800-LV05-03/F01 ebmpapst 400VAC 800mm EC Axial Fan

SKU: W3G800-LV05-03/F01

Price: \$2,954.13

Categories: Fans

Tags: ebmpapst

Product Link:

<https://www.electspares.com/product/w3g800-lv05-03-f01-ebmpapst-400vac-800mm-ec-axial-fan/>

Product Description

The ebmpapst W3G800-LV05-03/F01 is a high-capacity industrial EC axial fan with a nominal voltage of 400 VAC and dimensions of 970 x 970 x 350 mm, specifically engineered for large-scale air handling units and industrial cooling applications requiring high static pressure. Driven by a high-torque M3G150-NA GreenTech EC external rotor motor with a maximum power consumption of 3500 W and a current draw of 5.3 A, this unit features a heavy-duty dual ball bearing system designed for long-term mechanical stability and continuous S1 duty. Its advanced aerodynamic design, incorporating PP plastic guide vanes and an internal diffuser, delivers a powerful balance of massive airflow and high back pressure up to 350 Pa, making it highly effective at maintaining air circulation in industrial halls and commercial HVAC systems. Constructed with a galvanized and black plastic-coated sheet steel housing and a die-cast aluminum electronics enclosure, this 51.4 kg fan provides a dependable and energy-saving cooling solution with integrated Modbus-RTU interface and thermal overload protection for data centers and large-scale infrastructure at the end.

[W3G800-LV05-03/F01] Fan Parameters

Model Number: W3G800-LV05-03/F01

Manufacturer: ebmpapst

Motor Model: M3G150-NA

Series: W3G Series

Type: EC Axial Fan

Impeller Size: 800 mm

Dimensions: 970 x 970 x 350 mm

Weight: 51.4 kg

Bearing Type: Ball bearing

Nominal Voltage: 400 VAC (3-phase)

Voltage Range: 380 - 480 VAC

Frequency: 50 / 60 Hz

Power Consumption: 3500 W

Nominal Current: 5.3 A

Speed: 1190 RPM

Max. Air Flow: 62.23 CFM (105.7 m³/h / 1.76 m³/min)

Max. Static Pressure: 9.81 mmH₂O (96.24 Pa / 0.39 inH₂O)

Actual Air Flow: 19225 m³/h (@ optimum efficiency)

Actual Static Pressure: 350 Pa (Max. back pressure)

Overall Efficiency (η_{es}): 56.6 %

Motor Design: Brushless EC motor (External rotor)

Motor Protection: Thermal overload protection for electronics/motor; Line undervoltage / phase failure detection; Motor current limitation

Technical Features: MODBUS V6.3 (RS-485 MODBUS-RTU); Integrated PI controller; Soft start; External 15-50 VDC input; Alarm relay; Operation/Alarm LED; Configurable I/O; 3.3-24 VDC voltage output

Insulation Class: Class F

Electrical Hookup: Terminal box

Number of Blades: 5

Blade Pitch: 0°

Direction of Rotation: Clockwise, viewed toward rotor

Airflow Direction: V (Exhaust over struts)

Impeller Material: PP plastic

Housing Material: Sheet steel, galvanized and plastic-coated (RAL 9005)

Electronics Housing: Die-cast aluminum, painted gray

Guide Vanes Material: PP plastic

Internal Diffuser Material: PP plastic

Guard Grille Material: Steel, plastic-coated (RAL 9005)

Installation Position: Shaft horizontal or rotor on bottom

Degree of Protection: IP55

Environmental Protection: H2

Operating Temperature: -40 - +60 °C

Storage Temperature: -40 - +80 °C

Standard Compliance: EN 61800-5-1; CE; EN 61000-6-2/3

Approval Agency: EAC; UL 1004-7; CSA C22.2 No. 77

Application

The ebmpapst W3G800-LV05-03/F01 EC fan is primarily utilized in large air handling units, industrial ventilation systems, data center cooling walls, and rooftop HVAC heat exchangers.

Product Images





Scan for product details:

